



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/718,466	11/19/2003	Teng-Chun Tsai	JCLA11486	1034
7590	09/20/2004		EXAMINER	
J.C. Patents, Inc. Suite 250 4 Venture Irvine, CA 92618			NGUYEN, GEORGE BINH MINH	
			ART UNIT	PAPER NUMBER
			3723	

DATE MAILED: 09/20/2004

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary	Application No. 10/718,466	Applicant(s) TSAI ET AL.	
	Examiner George Nguyen	Art Unit 3723	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☐ Responsive to communication(s) filed on ____.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-21 is/are pending in the application.
- 4a) Of the above claim(s) ____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) ____ is/are allowed.
- 6) ☒ Claim(s) 1-21 is/are rejected.
- 7) ☐ Claim(s) ____ is/are objected to.
- 8) ☐ Claim(s) ____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 19 November 2003 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some * c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. ____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|---|--|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. ____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date ____ | 6) <input type="checkbox"/> Other: ____ |

DETAILED ACTION

This application has been filed with formal drawings which are accepted to the examiner.

Claims 1-21 are presented for examination.

Priority

1. Receipt is acknowledged of papers submitted under 35 U.S.C. 119(a)-(d), which papers have been placed of record in the file.

Claim Rejections - 35 USC § 102



2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

3. Claims 1, 2, 6, 8, 11-16 are rejected under 35 U.S.C. 102(b) as being anticipated by Tolles et al.'6,220,942.

With reference to Figures 4, 5, and 7, Tolles discloses the claimed invention.



Art Unit: 3723

US 6,220,942 B1

5

FIG. 4 shows a preferred embodiment of a platen 41 of the invention. The platen 41 comprises a patterned surface whereon a polishing pad may be disposed. Generally, the patterned surface has features formed therein defining a raised area and a recessed area. In the embodiment shown in FIG. 4, the raised area consists of a plurality of protrusions 60 while the recessed area is a plurality of intersecting grooves 62 defined by the protrusions 60. More specifically, the recessed area consists of two parallel sets of equally spaced orthogonally intersecting grooves 62 in a checker-board pattern. Each groove 62 traverses the upper surface of the platen 41 from one perimeter to the another. Thus, the grooves 62 are not contained, or blocked, at either end. However, the present invention also contemplates an embodiment having blocked grooves.

The raised area of the platen 41, or protrusions 60, defines a pad mounting surface. Preferably, the protrusions 60 cooperate to provide a substantially planar mounting surface 64 along a common plane A for supporting a polishing pad 44 as shown in FIG. 5. The pad 44 is attached using a commercially available pressure sensitive adhesive (PSA). Thus, the present invention eliminates the bottom pad of prior art as discussed with reference to FIG. 1. Further, the necessary pad compliance, previously achieved by using a bottom pad, is now provided by the cooperation of the recessed and raised areas, or grooves 62 and protrusions 60, respectively. The protrusions 60 ensure sufficient rigidity (or stiffness) while the grooves 62 allow the proper proportion of pad compliance to accommodate a substrate's varying topography.

As noted above, the grooves 62 are preferably open at some point along their length to prevent vacuum adherence of the pad to the surface. Thus, the grooves 62 provide pathways between the platen 41 and the pad 44 which vent to the environment of the platen 41 as shown in FIG. 5. Such a construction anticipates the use of perforated pads such as those available from Rodex. The perforations in the pad allow fluid flow therethrough. Where the grooves 62 are isolated from the environment, such as where the grooves 62 comprise concentric circles enclosed at the top by a perforated pad, a partial vacuum condition may be created in the grooves 62 as a substrate is urged against the pad. In such a case, the substrate remains clucked to the pad after the polishing cycle making it difficult to remove. By constructing the grooves 62 as shown in FIGS. 4 and 5, the grooves 62 remain at equal pressure to the ambient environment allowing easy declucking of the substrate. Where a concentric pattern is desired, a vent channel or channels extending to the perimeter of the platen 41 can be provided to eliminate adhesion between the substrate and platen 41. Such an embodiment is shown in FIG. 6 and described in detail below.

Preferably, the protrusions 60 and the grooves 62 shown in FIGS. 4 and 5 are defined by machining away a portion of the upper surface of the platen 41 which comprises a metal such as aluminum. However, the present invention also contemplates alternative embodiments. For example, the plurality of protrusions 60 may be constructed separately from the platen 41. The protrusions 60 may then be secured to the platen 41 surface by conventional methods such as brazing or welding. In another alternative, the platen 41 may comprise two separable plates with a lower plate secured to the motor 46 (shown in FIG. 3) and an upper plate comprising the patterned surface for mounting the pad 44. The plates may be permanently coupled by such methods as welding, or they may be detachably coupled by temporary fasteners or clamps. The latter embodiment provides a versatile platen assembly having an exchangeable mounting surface.

6

The dimensions of the patterned surface may be varied to achieve the desired proportions of compliance and rigidity. In general, the mounting surface 64 makes up to between about 20 to 95% of the total upper surface area but may be varied according to the pad thickness and modulus, as well as the applied polishing pressure. In a specific embodiment shown in FIG. 4 having a diameter of about twenty (20) inches, the groove depth is about 0.250 inches and the groove width is about 0.062 inches. Thus, the total surface area of the mounting area 64 is preferably about 20-95% of the total area of the platen. The diameter of the platen 41 may be varied to accommodate any substrate size such as 100 mm, 200 mm or 300 mm substrates. As a result, relative sizes of the grooves and protrusions will vary accordingly.

It is to be understood that the present invention allows for virtually limitless design variations. FIG. 4 and 5 show only one possible embodiment according to the invention. Another embodiment is shown in FIG. 6. In general, the embodiment of FIG. 6 provides a raised area and recessed area of the platen 41. Specifically, the platen 41 comprises a plurality of "broken" concentric grooves 65 intersected by radial grooves 66. The radial grooves 66 originate at a central hub 67 thereby communicating all of the features of the recessed area. The embodiments described above are merely illustrative and a person skilled in the art will recognize other embodiments within the scope of the present invention.

In addition to patterning the upper surface of the platen, a patterned mat, liner or other coating could be applied to or disposed over a typical platen as shown in FIGS. 7 and 8. A hard rubber-like coating could be molded or otherwise formed to provide one of the patterned surfaces described above. Thus, FIG. 7 shows a patterned mat 100 disposed on a platen 102 and having a polishing pad 103 disposed on an upper patterned mounting surface 104. In the specific embodiment shown, the patterned mat 100 has a surface profile similar to that of the platen 41 shown in FIG. 4 and described above, however, any pattern may be used to advantage. In such an embodiment, the platen 102 preferably comprises an untextured mounting surface (as shown in FIG. 7) for securing the patterned mat 100 thereto but may also comprise a patterned surface to cooperate with the patterned mat 100 in providing additional flexibility and compliance. The polishing pad 103, patterned mat 100, and platen 102 are secured to one another by any conventional methods such as by an adhesive.

FIG. 8 is a partial cross sectional view of an alternative embodiment comprising a coating 110 disposed on a patterned platen 112. The particular surface profile of the platen 112 shown in FIG. 8 is similar to that of the platen 41 shown in FIG. 4 but it is to be understood that any pattern may be used to advantage, such as those shown in FIGS. 4-7. The coating 110 may be secured to the platen 112 by conventional methods such as by an adhesive. A polishing pad (not shown) may then be secured to the upper mounting surface 114 defined by the coating 110 and platen 112.

The material used for the patterned mat 100 and coating 110 is preferably determined according to the material of the platen. In general, the patterned mat 100 and coating 110 comprise a material more compliant than the platen. For example, where the platen is made of a metal, such as aluminum or stainless steel, the patterned mat 100 and coating 110 may comprise an elastomer such as rubber. Other materials which are known and unknown could be used to advantage.

It is to be understood that terms such as top, bottom, below, above, backside and the like are relative terms and

4. Claims 18-20 are rejected under 35 U.S.C. 102(b) as being anticipated by Tolles et al.'6,217,426.

With reference to Figures 4, 5, 7, 9, and 11, Tolles discloses the claimed invention.




Fig. 4




Fig. 5




Fig. 7





Fig. 8



Claim Rejections - 35 USC § 103

5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

6. Claims 3-5, 7, 9-10, 17, and 21 are rejected under 35 U.S.C. 103(a) as being unpatentable over Tolles et al.'942 in view of Wang'6,666,751 and Tolles et al.'426.

Tolles et al.'942 has been discussed above, but does not disclose that both surfaces of the sub-polishing pad are undulating.

With reference to Figure 10, Wang discloses that the sub-polishing pad 95 having undulating interfacing surface 101 with the polishing platen 88. The advantage is to significantly enhance the polishing uniformity of the CMP process and substantially reduces any edge effects.




Fig. 10

Art Unit: 3723

Thus, it would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the sub-polishing pad of Tolles with platen interfacing surface having undulating surface as taught by Wang in order to significantly enhance the polishing uniformity of the CMP process and substantially reduces any edge effects.

Regarding to claim 5, 10, 21, it would have been obvious to one having ordinary skill in the art at the time the invention was made to have utilized fixed abrasive , since it had been held to be within the general skill of a worker in the art to select a known material on the basis of it suitability for the intended use as a matter of obvious design choice.

Regarding to claims 3, 9, 13, 16, it would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the undulating surface of Tolles'942 with different groove configuration as taught by Tolles'426 in order to significantly enhance the polishing uniformity.

Conclusion

7. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure. Nakata et al.'989, Breivogel et al.'910, Yamamoto'317, Yu'699, Tolles et al.'825 all disclose polishing pad with with undulating surface.


Any inquiry concerning this communication or earlier communications from the examiner should be directed to George Nguyen whose telephone number is 703-308-0163. The examiner can normally be reached on Monday-Friday/630AM-300PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Joseph Hail can be reached on 703-308-2687. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

George Nguyen
Primary Examiner
Art Unit 3723

GN – September 15, 2004



GEORGE NGUYEN
PRIMARY EXAMINER